


Thermal Printer

SLP600 Series



SLP620

- 300 dpi (650/650SE), 203dpi (620)
- 100mm/s (650/650SE), 70mm/s (620)
- USB (650/620), Serial and USB (650SE)

| Model | | SLP 620 | SLP 650/650SE |
|----------------------------|--------------------------|--|------------------------------|
| Printing | Method | direct thermal | |
| | Resolution dpi (dots/mm) | 203 (8) | 300 (11.81) |
| | Paper width (mm) max | 57.9 | |
| | Printing width (mm) max | 48 | 48.8 |
| | Speed (mm/s) | 70* | 100* |
| Barcode | | Code39, I-2 of 5, Code128, EAN13, EAN128, UPC-A, UPC-E, Codabar, Maxi Code, PDF417, Data Matrix, QR Code | |
| Communication Interface | | USB | 650 USB / 650SE USB, RS-232C |
| Power Supply (V) DC | | 5.7 to 6.3 | 11.4 to 12.6 |
| Current consumption (A) | Normal | 2.3 | 2.8 |
| | Maximum | 2.5 | 3.0 |
| Service life | Abrasion resistance (km) | 6 | 15 |
| Operating temperature (°C) | | 5 to 40 | |
| Storage temperature (°C) | | -20 to 60 | |
| Dimensions (W x D x H mm) | | 113.8 x 172.0 x 148.0 | |
| Mass (g) | | ca. 490 | |
| Software | | Windows® 2000, 2003, XP, Vista, 7 / Mac OS X | |



SLP650

SLP650SE



Specifications are subject to change without notice.

